

TORQUE WRENCHES

2400 ELOMETER Torque Wrench UDS

The new Torque Wrench Model ELOMETER-UDS with dial indicator and follow-up pointer.



2400 ELOMETER Torque Wrench UDS



Application	for left and right hand use
Type	with fixed head square, dial indicator and follow-up pointer, accuracy $\pm 2\%$ within 20%-100% of measuring range
Standard	according to DIN / ISO 6789

Stock-No.	Drive	Range Nm	Range in.lb.	Range ft.lb.	Pitch Nm	Pitch in.lb.	Pitch ft.lb.	Signal	mm	g
2400-UDS 3	1/4"	0 – 3,5	0 – 30	–	0,1	1	-	-	270	725
2400-UDS 9	1/4"	0 – 9	0 – 75	–	0,2	1	-	-	270	725
2400-UDS 18	3/8"	0 – 18	0 – 150	–	0,5	2	-	-	270	725
2400-UDS 30	3/8"	0 – 30	0 – 250	–	0,5	5	-	-	270	725
2400-UDS 70	3/8"	0 – 70	–	0 – 50	2	-	1	-	270	725
2400-UDS 240	1/2"	0 – 240	–	0 – 175	5	-	5	-	560	1400
2400-UDS 350	1/2"	0 – 350	–	0 – 250	10	-	5	-	560	1400
2400-UDS 480	3/4"	0 – 480	–	0 – 350	10	-	10	-	675	3200
2400-UDS 800	3/4"	0 – 800	–	0 – 600	25	-	10	-	1180	4500
2400-UDS 1400	1"	0 – 1400	–	0 – 1000	25	-	20	optical and acoustical	1970	9000
2400-UDS 2800	1"	0 – 2800	–	0 – 2000	50	-	40	optical and acoustical	3200	21000