

MS-22 Module



Application	For roller tool cabinet CADDY, Stock-No. 1200, BUDDY, Stock-No. 1210 and SUPER-CADDY, Stock-No. 1220
Type	Black, with transparent cover
Material	ABS
Stock-No.	Contents

MS-22	TOP-KRAFT-Pliers		
	495MB-185	Combination plier	1 870
	470MB-200	Flat round plier	
	490MB-165	Diagonal cutter	
	132-240	Waterpump plier	

478A Relay Adjusting Plier



Application	for bending of contact and relay springs
Type	chrome plated, polished, red cushion grip handles
Material	high grade tool steel C 45, Code No. 1.0503
Standard	according to DIN 5235 form A, flat pointed jaws

Stock-No.	mm		g
478A	135	1	75

478B Relay Adjusting Plier



Application	for bending of contact and relay springs
Type	chrome plated, polished, red cushion grip handles
Material	high grade tool steel C 45, Code No. 1.0503
Standard	according to DIN 5235 form B, flat wide jaws

Stock-No.	mm		g
478B	135	1	75

478C Relay Adjusting Plier



Application	for bending of contact and relay springs
Type	chrome plated, polished, red cushion grip handles
Material	high grade tool steel C 45, Code No. 1.0503
Standard	according to DIN 5235 form C, flat wide jaws, 45° bent

Stock-No.	mm		g
478C	135	1	75

478E Relay Adjusting Plier



Application	for bending of contact and relay springs
Type	chrome plated, polished, red cushion grip handles
Material	high grade tool steel C 45, Code No. 1.0503
Standard	according to DIN 5235 form E, flat wide jaws, 90° bent

Stock-No.	mm		g
478E	135	1	75

495 Combination Plier



Application	for hard wire
Type	MB: chrome plated, BI: chrome plated, polished, insulated TOP-KRAFT 2K plastic handles with slip guards
Material	high grade tool steel C 45, Code No. 1.0503
Standard	according to DIN / ISO 5746, form A/ISO 5746

Stock-No.	mm		g
495MB-165	165	1	170
495BI-165	165	1	200
495MB-185	185	1	230
495BI-185	185	1	260
495MB-205	205	1	290
495BI-205	205	1	320

493 Multi Purpose Plier "FIT"



Application	combination of plier and tinsnip
Type	black, with red transparent insulated handles
Material	high grade tool steel C 45, Code No. 1.0503

Stock-No.	mm		g
493	200	1	285


490 Heavy Duty Diagonal Cutter



Application	for piano wire
Type	MB: chrome plated, BI: chrome plated, polished, insulated TOP-KRAFT 2K plastic handles with slip guards
Material	Chrome-Vanadium 80 CrV 2, Code No. 1.2235
Standard	according to DIN 5238, form A/H/ISO 5749, slip joint pattern

Stock-No.	for piano wire up to Ø mm	mm		g
490MB-145	1,6	145	1	150
490BI-145	1,6	145	1	175
490MB-165	1,6	165	1	200
490BI-165	1,6	165	1	230
490MB-200	2,0	200	1	250
490BI-200	2,0	200	1	285

491 End Cutter



Type	black finish, induction hardened cutting edges. PVC dipped handles
Material	high grade tool steel C 60, Code No. 1.0601

Stock-No.	for hard wire up to Ø mm	mm		g
491-200AI	2	200	1	325
491-260AI	3	260	1	610

485 Heavy Duty End Cutter



Application	for hard wire
Type	MB: chrome plated, BI: chrome plated, polished, insulated TOP-KRAFT 2K plastic handles with slip guards
Material	high grade tool steel C 60, Code No. 1.0601
Standard	according to DIN / ISO 5748, slip joint pattern

Stock-No.	for hard wire up to Ø mm	mm		g
485MB	1,6	160	1	200
485BI	1,6	160	1	220