



|            |   |     |   |  |     |
|------------|---|-----|---|--|-----|
| Type       | jaws parallel in all positions, nickel plated |     |   |  |     |
| Stock-No.  | Capacity mm                                   | mm  |   |  | g   |
| <b>501</b> | 45  | 250 | 1 |  | 575 |



|               |                                       |     |   |  |     |
|---------------|---------------------------------------|-----|---|--|-----|
| Application   | parallel joint jaws                   |     |   |  |     |
| Type          | forged jaws 80 mm wide, nickel plated |     |   |  |     |
| Stock-No.     | Capacity mm                           | mm  |   |  | g   |
| <b>506-50</b> | 25                                    | 255 | 1 |  | 705 |



|                |                            |     |   |  |     |
|----------------|----------------------------|-----|---|--|-----|
| Type           | curved jaws, nickel plated |     |   |  |     |
| Stock-No.      | Capacity mm                | mm  |   |  | g   |
| <b>502-180</b> | 45                         | 180 | 1 |  | 365 |
| <b>502-250</b> | 45                         | 250 | 1 |  | 570 |



|                 |   |                 |     |   |     |
|-----------------|---|-----------------|-----|---|-----|
| Application     | for use instead of clamps, for use with many awkward shapes, <b>507-165S</b> with flexible steel jaws |                 |     |   |     |
| Type            | nickel plated   |                 |     |   |     |
| Stock-No.       | Capacity mm   | Radial range mm | mm  |   |     |
| <b>507-165</b>  | 0-60  | 45              | 165 | 1 | 230 |
| <b>507-165S</b> | 0-50  | 45              | 165 | 1 | 250 |



|                |  |                    |                 |   |      |
|----------------|--|--------------------|-----------------|---|------|
| Application    | for use of even small round parts  |                    |                 |   |      |
| Type           | jaws parallel in all positions, stepless adjustment up to 100 respect. 200 mm, nickel plated |                    |                 |   |      |
| Stock-No.      | mm   | Clamping height mm | Radial range mm |   |      |
| <b>505-100</b> | 280  | 100                | 65              | 1 | 950  |
| <b>505-200</b> | 280  | 200                | 65              | 1 | 1100 |



|             |  |   |  |  |  |
|-------------|--|---|--|--|--|
| Application | to protect delicate surfaces, for use with Parallel-Grip Plier Stock-No. 505 |   |  |  |  |
| Stock-No.   |  |   |  |  |  |
| <b>505K</b> | 2  | 5 |  |  |  |